# INDUSTRIAL ENCLOSURES **BY TRICEL**







IP43 SINGLE DOOR ELECTRICAL ENCLOSURE 1000 x 750 x 300MM SINGLE DOOR COMPLIES TO IEC 62208:2011 STOCK CODE: 103968



### **IP43 SINGLE DOOR ECTRICAL ENCLOSURE**

Suitable for electrical and commercial installations.

Complies with the international standard for empty enclosures as applied to low-voltage switchgear and control gear assemblies (IEC 62208:2011).



Example: photovoltaic nh-fuses

## INDUSTRIAL ENCLOSURES

TECHNICAI

#### INTERNAL DIMENSIONS & CAPACITY

Dimensions: 1000mm high x 750mm wide x 300mm deep The overall height of this box is 1066mm and overall width is 754mm. The opening size is 971mm x 678mm\*

#### SPECIFICATION & KEY FEATURES

- Electromagnetic compatibility, ideal for protecting internal electronic communication.
- · Suitable for low-voltage switchgear and control gear assemblies, meters, compressors, etc.
- Will not corrode, weather resistant to IP43 grade protection.
- High impact resistance up to 20 Kilojoules (IK10).
- Double insulation and electrically non-conductive (1000V).
- Triple lock system supported by non-corrosive vertical bars.
- Door hinges on right, 180° opening.
- · Easily cleaned and can be painted.
- Constructed from GRP.
- Supplied with hinges, lock and key.
- Supplied fully assembled, complete with backboard and triple lock system.
- Supplied in light grey colour (Ral 7035).
- Suitable for use in temperatures ranging from -30°C to +70°C.
- Made from non-hygroscopic material ensuring minimum water absorption.
- · Constructed from halogen-free and self-extinguishing material.
- · UV protected.



\* Approximate dimensions.

In accordance with Tricel's normal policy of product development these specifications are subject to change without notice.

## IP43 SINGLE DOOR ELECTRICAL ENCLOSURE

#### **ASSOCIATED PRODUCTS**



PLINTH (104033)



40t **TECHNICAL EXPERIENCE** 



TRICEL IRL