



TRICEL
WATER STORAGE

One piece tanks



Insulated F30, One piece water tanks, ranging from 45 to 4,546 litre (10 - 1.000 gallons) nominal. Non-standard sizes are also available, to customer specifications.

Many local authorities, consultants, engineers and contractors specify and use our fibreglass insulated F30 tanks, secure in the knowledge that both they and their clients are in safe hands, and helping them meet their health and safety obligations. In order to comply with health and safety directives, which states that water, that may be consumed by humans, must be held in Insulated tanks, and that all tanks must meet the following criteria.

- Factory insulated with CFC Free Foam on all sides
- Fibreglass in construction
- Lids must be sealed and insulated
- Suitable for Potable (drinking) water
- Tanks must have screened inlet and overflows
- Tanks to be insulated to reduce the risk of freezing in winter and assist in keeping the water temperature low in summer time
- Have suitable fibreglass condensation trays, plumbed to an overflow

Also from Tricel (Killarney)

- Sectional water storage tanks
- Custom moulding, access chambers, safety products
- Underground and overground storage tanks
- Tricel Novo - wastewater treatment systems
- Kiosks
- Insulated housings
- Metering cabinets (electrical and gas)

| Model | Length | Width | Height | Height if Insulated | Litres nominal | Gallons nominal |
|---------|--------|-------|--------|---------------------|----------------|-----------------|
| KP10 | 495 | 370 | 345 | 420 | 45 | 10 |
| KP20 sq | 610 | 485 | 445 | 520 | 91 | 20 |
| KP25 | 1200 | 530 | 340 | 420 | 114 | 25 |
| KP40 lg | 1041 | 546 | 457 | 457 | 182 | 40 |
| KP40 sq | 670 | 530 | 565 | 640 | 182 | 40 |
| KP50 | 1216 | 545 | 457 | 545 | 227 | 50 |
| KP70 | 1230 | 575 | 584 | 650 | 318 | 70 |
| KP100 | 1448 | 740 | 610 | 685 | 454 | 100 |
| KP100/2 | 1040 | 761 | 700 | 736 | 454 | 100 |
| KP150 | 1645 | 1075 | 545 | 610 | 682 | 150 |
| KP200 | 1660 | 1055 | 690 | 765 | 909 | 200 |
| KP200/2 | 1270 | 1000 | 860 | 900 | 909 | 200 |
| KP250 | 1660 | 1055 | 845 | 920 | 1136 | 250 |
| KP300 | 1660 | 1245 | 845 | 1015 | 1363 | 300 |
| KP400 | 2545 | 1330 | 615 | 775 | 1818 | 400 |
| KP500 | 1880 | 1375 | 1140 | 1300 | 2275 | 500 |
| KP800 | 2690 | 1830 | 1040 | 1040 | 3637 | 800 |
| KP1000 | 2690 | 1830 | 1290 | 1290 | 4546 | 1000 |

Please note: Insulation slows down, but does not prevent heat loss or heat gain, over protracted periods. Additional information is available in BS 7491 & BS 6700.



TRICEL
GENERATIONS OF INNOVATION

Tricel (Killarney) Unlimited Company, Ballyspillane Industrial Estate, Killarney, Co. Kerry, Ireland.
Tel: +353 (0) 64 6632421 | Email: sales@ie.tricel.eu | www.ie.tricel.eu

In accordance with Tricel's normal policy of product development these specifications are subject to change without notice.