



TRICEL
WATER STORAGE

One piece tanks



Insulated F30, One piece water tanks, ranging from 45 to 4,546 litre (10 - 1.000 gallons) nominal. Non-standard sizes are also available, to customer specifications.

Many local authorities, consultants, engineers and contractors specify and use our fibreglass insulated F30 tanks, secure in the knowledge that both they and their clients are in safe hands, and helping them meet their health and safety obligations. In order to comply with health and safety directives, which states that water, that may be consumed by humans, must be held in Insulated tanks, and that all tanks must meet the following criteria.

- Factory insulated with CFC Free Foam on all sides
- Fibreglass in construction
- Lids must be sealed and insulated
- Suitable for Potable (drinking) water
- Tanks must have screened inlet and overflows
- Tanks to be insulated to reduce the risk of freezing in winter and assist in keeping the water temperature low in summer time
- Have suitable fibreglass condensation trays, plumbed to an overflow

Also from Tricel (Killarney)

- Sectional water storage tanks
- Custom moulding, access chambers, safety products
- Underground and overground storage tanks
- Tricel Novo - wastewater treatment systems
- Kiosks
- Insulated housings
- Metering cabinets (electrical and gas)

Model	Length	Width	Height	Height if Insulated	Litres nominal	Gallons nominal
KP10	495	370	345	420	45	10
KP20 sq	610	485	445	520	91	20
KP25	1200	530	340	420	114	25
KP40 lg	1041	546	457	457	182	40
KP40 sq	670	530	565	640	182	40
KP50	1216	545	457	545	227	50
KP70	1230	575	584	650	318	70
KP100	1448	740	610	685	454	100
KP100/2	1040	761	700	736	454	100
KP150	1645	1075	545	610	682	150
KP200	1660	1055	690	765	909	200
KP200/2	1270	1000	860	900	909	200
KP250	1660	1055	845	920	1136	250
KP300	1660	1245	845	1015	1363	300
KP400	2545	1330	615	775	1818	400
KP500	1880	1375	1140	1300	2275	500
KP600-2	2030	1500	1322	1322	2700	600
KP800	2690	1830	1040	1040	3637	800
KP1000	2690	1830	1290	1290	4546	1000

Please note: Insulation slows down, but does not prevent heat loss or heat gain, over protracted periods. Additional information is available in BS 7491 & BS 6700.



TRICEL
GENERATIONS OF INNOVATION

Tricel (Killarney) Unlimited Company, Ballyspillane Industrial Estate, Killarney, Co. Kerry, Ireland.
Tel: +353 (0) 64 6632421 | Email: sales@ie.tricel.eu | www.ie.tricel.eu

In accordance with Tricel's normal policy of product development these specifications are subject to change without notice.